SOLAR LINE IMPEDANCE STABILIZATION NETWORK


SOLAR TYPE 21314-50-R-25-BNC

Specifications:

Current rating: ..... 25 amperes
Inductance: ..... 50 µH
Frequency range (recommended): ..... 150 kHz – 30 MHz
Voltage (line to ground): ..... 400 VDC, 270 V 50-60 Hz, 135 V 400 Hz
Power connections: ..... NEMA 5-20 AC receptacle and line cord
RF connector: ..... Type BNC
Coupling capacitor: ..... 0.10 µF
Circuit: ..... Dual
Case size: ..... 13.48" x 7.25" x 13.25" (34.24 cm x 18.42 cm x 33.66 cm)
Overall length with base plate: 17.25" (43.82 cm)

Remarks: Designed for CISPR 16-1-2 Ed. 1.2. Switch provided for testing for each line, terminating other line into 50 ohms. Specifications subject to change without notice.

Rev. September 3, 2016



SOLAR ELECTRONICS COMPANY
A Division of A.T. Parker, Inc.
10866 Chandler Boulevard, North Hollywood, CA 91601

YiFengTech 亦锋科技
地址： 北京市亦庄经济技术开发区宏达中路16号宏达三鼎工业区写字楼309室 电话： 010 - 67886078 传真： 010 - 67891690 邮箱： inquiry@yifengtech.com.cn