SOLAR LINE IMPEDANCE STABILIZATION NETWORK


SOLAR TYPE 21407-5-TS-50-N

Specifications:

Current rating: ..... 50 amperes
Inductance: ..... 5 µH
Frequency range (recommended): ..... 100 kHz - 100 MHz
Voltage (line to ground): ..... 600 VDC, 500 V 50 - 60 Hz, 240 V 400 Hz
Power connections: ..... TS ¼-20 threaded stud
RF connector: ..... Type N (2)
Coupling capacitor: ..... 0.10 µF
Circuit: ..... Single
Case size: ..... 10.29" x 9.25" x 13.00" (26.14 cm x 23.50 cm x 33.02 cm)
Overall length with base plate: 17.00" (43.18 cm)

Remarks: Designed for CISPR 25. Specifications subject to change without notice.

Rev. September 3, 2016



SOLAR ELECTRONICS COMPANY
A Division of A.T. Parker, Inc.
10866 Chandler Boulevard, North Hollywood, CA 91601
YiFengTech 亦锋科技
地址： 北京市亦庄经济技术开发区宏达中路16号宏达三鼎工业区写字楼309室 电话： 010 - 67886078 传真： 010 - 67891690 邮箱： inquiry@yifengtech.com.cn